



Ware washing – Water Temps & Sanitizer Log

(This log is to be completed daily by staff and verified daily by the site supervisor or manager)

School: _____

Manager: _____

Wash Water Minimum Temp *SEE BELOW*

• Final Rinse - 180° for Hot Water Sanitizing • Chemical Sanitizing must 50-100 ppm of Chlorine Solution

| | DATE | TIME | WASH CYCLE TEMP | FINAL RINSE TEMP | CHEMICAL SANITIZER PPM | CORRECTIVE ACTION Note: If water temp or sanitizer levels are below the guidelines | INITIALS | MANAGER VERIFICATION |
|----|------|------|-----------------|------------------|------------------------|---|----------|----------------------|
| 1 | | | | | | | | |
| 2 | | | | | | | | |
| 3 | | | | | | | | |
| 4 | | | | | | | | |
| 5 | | | | | | | | |
| 6 | | | | | | | | |
| 7 | | | | | | | | |
| 8 | | | | | | | | |
| 9 | | | | | | | | |
| 10 | | | | | | | | |
| 11 | | | | | | | | |
| 12 | | | | | | | | |
| 13 | | | | | | | | |
| 14 | | | | | | | | |
| 15 | | | | | | | | |

Ware washing Machines using Chemical Sanitizers must have a wash water temperature not below 150°

Machines using HOT water to sanitize must meet one of the following temperature guidelines depending on the type of machine in use:

- Stationary rack, single temperature machine – 165°
- Stationary rack, dual temperature machine – 150°
- Single tank, conveyor, dual temperature machine – 160°
- Multi-tank, conveyor, multitemperature machine - 150°

